



JIS 16K RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.2	12	70	52	1	4	15	0.53
DN 20	¾"	100	27.7	14	75	58	1	4	15	0.69
DN 25	1"	125	34.5	14	90	70	1	4	19	1.07
DN 32	1¼"	135	43.2	16	100	80	2	4	19	1.35
DN 40	1½"	140	49.1	16	105	85	2	4	19	1.43
DN 50	2"	155	61.1	16	120	100	2	8	19	1.59
DN 65	2½"	175	77.1	18	140	120	2	8	19	2.27
DN 80	3"	200	90	20	160	135	2	8	22	3.25
DN 100	4"	225	115.4	22	185	160	2	8	22	4.30
DN 125	5"	270	141.2	22	225	195	2	8	25	6.17
DN 150	6"	305	166.6	24	260	230	2	12	25	8.19
DN 200	8"	350	218	26	305	275	2	12	25	10.39
DN 250	10"	430	269.5	28	380	345	2	12	29	17.05
DN 300	12"	480	321	30	430	395	3	16	29	20.05
DN 350	14"	540	358.1	34	480	440	3	16	32	29.47
DN 400	16"	605	409	38	540	495	3	16	35	40.32
DN 450	18"	675	460	40	605	560	3	20	35	52.26
DN 500	20"	730	511	42	660	615	3	20	35	61.97
DN 550	22"	795	562	44	720	670	3	20	38	75.51
DN 600	24"	845	613	46	770	720	3	24	38	83.59