



ANSI 150LBS THREADED FLANGE

Size		Flange				Slip On		Raised Face	Drilling		Weight	
mm	inch	D	I	T	K	E	M	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	89.0	15.9	9.5	60.3	15.9	30.2	35.0	1.6	4	15.8	0.40
DN 20	¾"	98.5	15.9	11.2	69.8	15.9	38.2	42.9	1.6	4	15.8	0.57
DN 25	1"	108.0	17.5	12.7	79.3	17.5	49.2	50.9	1.6	4	15.8	0.78
DN 32	1¼"	117.5	20.7	14.3	88.9	20.7	58.8	63.6	1.6	4	15.8	1.05
DN 40	1½"	127.1	22.3	15.9	98.4	22.3	65.1	73.1	1.6	4	15.8	1.33
DN 50	2"	152.5	25.5	17.5	120.6	25.5	77.8	92.0	1.6	4	19.0	2.06
DN 65	2½"	177.9	28.6	20.7	139.7	28.6	90.5	104.8	1.6	4	19.0	3.31
DN 80	3"	190.6	30.2	22.2	152.4	30.2	108.0	127.1	1.6	4	19.0	3.90
DN 100	4"	228.7	33.4	22.2	190.5	33.4	135.0	157.2	1.6	8	19.0	5.35
DN 125	5"	254.1	36.5	22.2	215.9	36.5	163.5	185.8	1.6	8	22.2	6.10
DN 150	6"	279.5	39.7	23.9	241.3	39.7	192.1	216.0	1.6	8	22.2	7.50
DN 200	8"	343.0	44.5	27.0	298.4	44.5	246.1	269.9	1.6	8	22.2	12.17
DN 250	10"	406.5	49.2	28.6	361.9	49.2	304.9	323.9	1.6	12	25.4	16.61
DN 300	12"	482.7	55.6	30.2	431.8	55.6	365.2	381.1	1.6	12	25.4	26.33
DN 350	14"	533.5	57.2	33.4	476.2	57.2	400.1	412.8	1.6	12	28.5	34.78
DN 400	16"	597.0	63.6	34.9	539.7	63.6	457.3	470.0	1.6	16	28.5	45.10
DN 450	18"	635.1	68.3	38.1	577.8	68.3	504.9	533.5	1.6	16	31.7	49.15
DN 500	20"	698.6	73.1	41.3	635.0	73.1	558.9	584.3	1.6	20	31.7	62.29
DN 550	22"	749.4	79.4	44.5	692.1	79.4	609.7	641.4	1.6	20	34.9	72.29
DN 600	24"	812.9	82.6	46.1	749.3	82.6	663.6	692.2	1.6	20	34.9	87.48
DN 650	26"	869.9	85.7	49.2	806.4	85.7	723.9	742.9	1.6	24	34.9	104.6
DN 700	28"	927.1	87.3	50.8	863.6	87.3	781.0	793.7	1.6	28	34.9	119.48
DN 750	30"	984.2	88.9	52.4	914.4	88.9	831.8	857.2	1.6	28	34.9	135.26