



### JIS 5K FF BLIND

Size		Flange			Drilling		Weight
mm	inch	D	T	K	Bolt no.	H	Kg / Pc
DN 10	3/8"	75	9	55	4	12	0.28
DN 15	1/2"	80	9	60	4	12	0.32
DN 20	3/4"	85	10	65	4	12	0.41
DN 25	1"	95	10	75	4	12	0.52
DN 32	1 1/4"	115	12	90	4	15	0.92
DN 40	1 1/2"	120	12	95	4	15	1.00
DN 50	2"	130	14	105	4	15	1.39
DN 65	2 1/2"	155	14	130	4	15	2.01
DN 80	3"	180	14	145	4	19	2.69
DN 90	3 1/2"	190	14	155	4	19	3.01
DN 100	4"	200	16	165	8	19	3.68
DN 125	5"	235	16	200	8	19	5.19
DN 150	6"	265	18	230	8	19	7.51
DN 200	8"	320	20	280	8	23	12.17
DN 250	10"	385	22	345	12	23	19.35
DN 300	12"	430	22	390	12	23	24.35
DN 350	14"	480	24	435	12	25	33.17
DN 400	16"	540	24	495	16	25	41.90
DN 450	18"	605	24	555	16	25	52.98
DN 500	20"	655	24	605	20	25	61.98
DN 550	22"	720	26	665	20	27	81.22
DN 600	24"	770	26	715	20	27	93.23