



ANSI 150LBS SOCKET WELDED

Size		Flange						HUB	Raised		Drilling		Weight	
mm	inch	D	A	C	P	T	I	M	F	G	K	Bolt. N	H	Kg / Pc
DN 15	½"	88.9	22.4	15.7	9.5	11.1	15.9	30.2	1.6	34.9	60.3	4	15.9	0.46
DN 20	¾"	98.4	27.7	20.8	11.1	12.7	15.9	38.1	1.6	42.9	69.8	4	15.9	0.64
DN 25	1"	107.9	34.5	26.7	12.7	14.3	17.5	49.2	1.6	50.8	79.4	4	15.9	0.87
DN 32	1¼"	117.5	43.2	35.1	14.3	15.9	20.6	58.7	1.6	63.5	88.9	4	15.9	1.14
DN 40	1½"	127.0	49.5	40.9	15.9	17.5	22.2	65.1	1.6	73.0	98.4	4	15.9	1.45
DN 50	2"	152.4	62.0	52.6	17.5	19.1	25.4	77.8	1.6	92.1	120.6	4	19.0	2.28
DN 65	2½"	177.8	74.7	62.7	19.1	22.3	28.6	90.5	1.6	104.8	139.7	4	19.0	3.57
DN 80	3"	190.5	90.7	78.0	20.6	23.8	30.2	107.9	1.6	127.0	152.4	4	19.0	4.18
DN 100	4"	228.6	116.1	102.4	23.8	23.8	33.3	134.9	1.6	157.2	190.5	8	19.0	5.87
DN 125	5"	254.0	143.8	128.3	23.8	23.8	36.5	163.5	1.6	185.7	215.9	8	22.2	6.94
DN 150	6"	279.4	170.7	154.2	27.0	25.4	39.7	192.1	1.6	215.9	241.3	8	22.2	8.46
DN 200	8"	342.9	221.5	202.7	31.7	28.6	44.4	246.1	1.6	269.9	298.4	8	22.2	13.39
DN 250	10"	406.4	276.4	254.5	33.3	30.2	49.2	304.8	1.6	323.8	361.9	12	25.4	19.01
DN 300	12"	482.6	327.2	304.8	39.7	31.8	55.6	365.1	1.6	381.0	431.8	12	25.4	29.05
DN 350	14"	533.4	359.2	336.6	41.3	34.9	57.1	400.1	1.6	412.7	476.2	12	28.6	38.11
DN 400	16"	596.9	410.5	387.4	44.4	36.5	63.5	457.2	1.6	469.9	539.7	16	28.6	49.84
DN 450	18"	635.0	461.8	438.2	49.2	39.7	68.3	504.8	1.6	533.4	577.8	16	31.7	55.16
DN 500	20"	698.5	513.1	489.0	54.0	42.9	73.0	558.8	1.6	584.2	635.0	20	31.7	69.89
DN 600	24"	812.8	616.0	590.6	63.5	47.6	82.5	663.6	1.6	692.1	749.3	20	34.9	97.45