




DIN 2501 PN 40 RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.0	16	65	45	2	4	14	0.69
DN 20	¾"	105	27.6	18	75	58	2	4	14	0.97
DN 25	1"	115	34.4	18	85	68	2	4	14	1.16
DN 32	1¼"	140	43.1	18	100	78	2	4	18	1.68
DN 40	1½"	150	49.0	18	110	88	3	4	18	1.85
DN 50	2"	165	61.1	20	125	102	3	4	18	2.46
DN 65	2½"	185	77.1	22	145	122	3	8	18	3.19
DN 80	3"	200	90.3	24	160	138	3	8	18	4.01
DN 100	4"	235	115.9	24	190	162	3	8	22	5.18
DN 125	5"	270	141.6	26	220	188	3	8	26	7.05
DN 150	6"	300	170.5	28	250	218	3	8	26	8.95
DN 200	8"	375	221.8	34	320	285	3	12	30	16.09
DN 250	10"	450	276.2	38	385	345	3	12	33	25.35
DN 300	12"	515	327.6	42	450	410	4	16	33	34.60
DN 350	14"	580	359.7	46	510	465	4	16	36	50.66
DN 400	16"	660	411.0	50	585	535	4	16	39	72.03
DN 450	18"	685	462.0	50	610	560	4	20	39	66.76
DN 500	20"	755	513.6	52	670	615	4	20	42	83.48
DN 600	24"	890	615.0	60	795	735	5	20	48	130.44