




STAINLESS STEEL 150 LBS SCREWED FITTINGS

BSPP (ISO 228-1), BSPT (ISO 7-1), NPT THREAD

DIMENSION CONFORM TO ASME B16.3 AND ANSI/MSS SP-114-2018 WHERE APPLICABLE
MATERIAL CONFORM TO ASTM A351 GR. CF8 & CF8M
PRESSURE-TEMPERATURE RATINGS 300 PSI (-29 TO 66°C)
MADE BY LOST WAX INVESTMENT CASTING



REDUCED COUPLING

| Size | A1 | A2 | H | Weight |
|---------------|-------|-------|------|---------|
| | (mm) | (mm) | (mm) | (Kg/Pc) |
| 1/4"x1/8" | 17.3 | 14.0 | 25.6 | 0.02 |
| 3/8"x1/8" | 21.0 | 14.0 | 27.9 | 0.03 |
| 3/8"x1/4" | 21.0 | 18.0 | 28.0 | 0.04 |
| 1/2"x1/8" | 26.8 | 14.0 | 33.2 | 0.04 |
| 1/2"x1/4" | 26.8 | 18.0 | 33.2 | 0.04 |
| 1/2"x3/8" | 26.8 | 21.0 | 33.7 | 0.04 |
| 3/4"x1/4" | 32.3 | 18.0 | 33.7 | 0.06 |
| 3/4"x3/8" | 32.3 | 21.0 | 35.0 | 0.06 |
| 3/4"x1/2" | 32.3 | 26.8 | 35.0 | 0.07 |
| 1"x1/4" | 39.8 | 18.0 | 41.0 | 0.10 |
| 1"x3/8" | 39.8 | 21.0 | 41.0 | 0.10 |
| 1"x1/2" | 39.8 | 26.8 | 41.0 | 0.10 |
| 1"x3/4" | 39.8 | 32.3 | 41.0 | 0.11 |
| 1 1/4"x3/8" | 49.0 | 21.0 | 44.0 | 0.13 |
| 1 1/4"x1/2" | 49.0 | 26.8 | 45.0 | 0.14 |
| 1 1/4"x3/4" | 49.0 | 32.3 | 45.0 | 0.14 |
| 1 1/4"x1" | 49.0 | 39.8 | 46.0 | 0.15 |
| 1 1/2"x1/2" | 55.8 | 26.8 | 46.0 | 0.21 |
| 1 1/2"x3/4" | 55.8 | 32.3 | 46.5 | 0.20 |
| 1 1/2"x1" | 55.8 | 39.8 | 49.0 | 0.20 |
| 1 1/2"x1 1/4" | 55.8 | 49.0 | 50.0 | 0.21 |
| 2"x1/2" | 68.0 | 27.0 | 54.0 | 0.27 |
| 2"x3/4" | 68.0 | 32.0 | 54.0 | 0.29 |
| 2"x1" | 68.0 | 39.8 | 54.0 | 0.30 |
| 2"x1 1/4" | 68.0 | 49.0 | 57.2 | 0.31 |
| 2"x1 1/2" | 68.0 | 55.8 | 58.2 | 0.32 |
| 2 1/2"x1" | 90.0 | 40.0 | 60.2 | 0.57 |
| 2 1/2"x1 1/4" | 90.0 | 49.0 | 60.2 | 0.57 |
| 2 1/2"x1 1/2" | 90.0 | 55.8 | 59.5 | 0.59 |
| 2 1/2"x2" | 90.0 | 68.0 | 60.0 | 0.59 |
| 3"x1" | 100.0 | 40.0 | 61.4 | 0.59 |
| 3"x1 1/4" | 100.0 | 49.0 | 62.5 | 0.64 |
| 3"x1 1/2" | 100.0 | 55.8 | 62.5 | 0.64 |
| 3"x2" | 100.0 | 68.0 | 63.0 | 0.72 |
| 3"x2 1/2" | 100.0 | 90.0 | 69.0 | 0.86 |
| 4"x1 1/2" | 127.0 | 55.8 | 70.0 | 1.20 |
| 4"x2" | 127.0 | 68.0 | 70.0 | 1.20 |
| 4"x2 1/2" | 127.0 | 90.0 | 70.5 | 1.20 |
| 4"x3" | 127.0 | 100.0 | 75.5 | 1.20 |