



DIN 2632 PN 10 WNRF

Size		Pipe	Flange					Neck			Raised Face		Drilling		Weight		
mm	inch	d1	D	A	T	T - F	K	h1	h2	d3	s	r	F	G	Bolt No.	H	Kg / Pc
DN 15	½"	21.3	95	17.3	14	12	65	35	6	32	2.0	4	2	45	4	14	0.66
DN 20	¾"	26.9	105	22.3	16	14	75	38	6	40	2.3	4	2	58	4	14	0.96
DN 25	1"	33.7	115	28.5	16	14	85	38	6	45	2.6	4	2	68	4	14	1.15
DN 32	1¼"	42.4	140	37.2	16	14	100	40	6	56	2.6	6	2	78	4	18	1.67
DN 40	1½"	48.3	150	43.1	16	13	110	42	7	64	2.6	6	3	88	4	18	1.85
DN 50	2"	60.3	165	54.5	18	15	125	45	8	75	2.9	6	3	102	4	18	2.51
DN 65	2½"	76.1	185	70.3	18	15	145	45	10	90	2.9	6	3	122	4	18	3.06
DN 80	3"	88.9	200	82.5	20	17	160	50	10	105	3.2	8	3	138	8	18	3.86
DN 100	4"	114.3	220	107.1	20	17	180	52	12	131	3.6	8	3	158	8	18	4.45
DN 125	5"	139.7	250	131.7	22	19	210	55	12	156	4.0	8	3	188	8	18	6.12
DN 150	6"	168.3	285	159.3	22	19	240	55	12	184	4.5	10	3	212	8	22	7.47
DN 200	8"	219.1	340	207.3	24	21	295	62	16	235	5.9	10	3	268	8	22	11.20
DN 250	10"	273.0	395	260.4	26	23	350	68	16	292	6.3	12	3	320	12	22	15.05
DN 300	12"	323.9	445	309.7	26	22	400	68	16	344	7.1	12	4	370	12	22	17.63
DN 350	14"	355.6	505	341.4	26	22	460	68	16	385	7.1	12	4	430	16	22	23.92
DN 400	16"	406.4	565	392.2	26	22	515	72	16	440	7.1	12	4	482	16	26	28.98
DN 450	18"	457.0	615	442.8	28	24	565	72	16	488	7.1	12	4	532	20	26	33.36
DN 500	20"	508.0	670	493.8	28	24	620	75	16	542	7.1	12	4	585	20	26	38.61
DN 600	24"	610.0	780	595.8	28	23	725	80	18	642	7.1	12	5	685	20	30	46.97