



UNI 6089 PN 10

Size		Flange						Drilling		Weight
mm	inch	D	A	T	K	C	t	Bolt no.	H	Kg / Pc
DN 15	½"	95	25	12	65	1.0	3	4	14	0.56
DN 20	¾"	105	30	14	75	1.0	4	4	14	0.81
DN 25	1"	115	37	16	85	1.0	4	4	14	1.09
DN 32	1¼"	140	46	16	100	1.5	4	4	18	1.60
DN 40	1½"	150	52	16	110	1.5	4	4	18	1.82
DN 50	2"	165	64	16	125	1.5	4	4	18	2.15
DN 65	2½"	185	80	16	145	1.5	4	4	18	2.62
DN 80	3"	200	94	18	160	1.5	5	4	18	3.31
DN 100	4"	220	119	18	180	2.0	5	8	18	3.51
DN 125	5"	250	145	18	210	2.0	5	8	18	4.31
DN 150	6"	285	174	18	240	2.0	5	8	22	5.22
DN 200	8"	340	225	20	295	2.0	5	8	22	7.53
DN 250	10"	395	279	22	350	2.0	5	12	22	9.82
DN 300	12"	445	330	26	400	2.0	5	12	22	13.36
DN 350	14"	505	362	28	460	2.0	5	16	22	20.07
DN 400	16"	565	413	32	515	2.5	6	16	25	27.35
DN 450	18"	615	464	34	565	2.5	6	20	25	31.53
DN 500	20"	670	515	38	620	2.5	6	20	25	40.10
DN 600	24"	780	618	44	725	2.5	6	20	30	56.55