



DIN 2501 PN 16 RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	14	65	45	2	4	14	0.64
DN 20	¾"	105	16	75	58	2	4	14	0.93
DN 25	1"	115	16	85	68	2	4	14	1.14
DN 32	1¼"	140	16	100	78	2	4	18	1.66
DN 40	1½"	150	16	110	88	3	4	18	1.85
DN 50	2"	165	18	125	102	3	4	18	2.60
DN 65	2½"	185	18	145	122	3	4	18	3.34
DN 80	3"	200	20	160	138	3	8	18	4.30
DN 100	4"	220	20	180	158	3	8	18	5.29
DN 125	5"	250	22	210	188	3	8	18	7.71
DN 150	6"	285	22	240	212	3	8	22	9.95
DN 200	8"	340	24	295	268	3	12	22	15.63
DN 250	10"	405	26	355	320	3	12	26	24.14
DN 300	12"	460	28	410	378	4	12	26	33.82
DN 350	14"	520	30	470	438	4	16	26	46.60
DN 400	16"	580	32	525	490	4	16	30	61.85
DN 450	18"	640	32	585	550	4	20	30	75.48
DN 500	20"	715	34	650	610	4	20	33	100.26
DN 600	24"	840	36	770	725	5	20	36	146.93