



JIS 20K RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	14	70	52	1	4	15	0.67
DN 20	¾"	100	16	75	58	1	4	15	0.87
DN 25	1"	125	16	90	70	1	4	19	1.35
DN 32	1¼"	135	18	100	80	2	4	19	1.74
DN 40	1½"	140	18	105	85	2	4	19	1.89
DN 50	2"	155	18	120	100	2	8	19	2.22
DN 65	2½"	175	20	140	120	2	8	19	3.27
DN 80	3"	200	22	160	135	2	8	23	4.66
DN 100	4"	225	24	185	160	2	8	23	6.65
DN 125	5"	270	26	225	195	2	8	25	10.58
DN 150	6"	305	28	260	230	2	12	25	14.44
DN 200	8"	350	30	305	275	2	12	25	20.90
DN 250	10"	430	34	380	345	2	12	27	36.42
DN 300	12"	480	36	430	395	3	16	27	47.66
DN 350	14"	540	40	480	440	3	16	33	66.50
DN 400	16"	605	46	540	495	3	16	33	97.49
DN 450	18"	675	48	605	560	3	20	33	126.88
DN 500	20"	730	50	660	615	3	20	33	155.98
DN 550	22"	795	52	720	670	3	20	39	191.12
DN 600	24"	845	54	770	720	3	24	39	223.87