



## DIN 2576 PN 10

Size		Flange				Drilling		Weight
mm	inch	D	A	T	K	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.0	14	65	4	14	0.67
DN 20	¾"	105	27.6	16	75	4	14	0.94
DN 25	1"	115	34.4	16	85	4	14	1.12
DN 32	1¼"	140	43.1	16	100	4	18	1.63
DN 40	1½"	150	49.0	16	110	4	18	1.87
DN 50	2"	165	61.1	18	125	4	18	2.48
DN 65	2½"	185	77.1	18	145	4	18	3.01
DN 80	3"	200	90.3	20	160	4	18	3.79
DN 80	3"	200	90.3	20	160	8 (By Order)	18	3.79
DN 100	4"	220	115.9	20	180	8	18	4.01
DN 125	5"	250	141.6	22	210	8	18	5.44
DN 150	6"	285	170.5	22	240	8	22	6.59
DN 200	8"	340	221.8	24	295	8	22	9.30
DN 250	10"	395	276.2	26	350	12	22	11.92
DN 300	12"	445	327.6	26	400	12	22	13.69
DN 350	14"	505	359.7	28	460	16	22	20.47
DN 400	16"	565	411.0	32	515	16	26	27.67
DN 450	18"	615	462.3	38	565	20	26	35.57
DN 500	20"	670	513.6	38	620	20	26	40.43
DN 600	24"	780	615.5	40	725	20	26	53.58