



ANSI 300LBS SORF

Size		Flange					Slip On		Raised Face		Drilling		Weight
mm	inch	D	A	I	T	K	L	M	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95.3	22.3	22.3	12.7	66.6	8.0	38.2	35.0	1.6	4	15.8	0.65
DN 20	¾"	117.5	27.6	25.5	14.3	82.5	9.6	47.7	42.9	1.6	4	19.0	1.13
DN 25	1"	123.9	34.5	27.0	15.9	88.9	9.5	54.0	50.9	1.6	4	19.0	1.37
DN 32	1¼"	133.4	43.1	27.0	17.5	98.4	7.9	63.6	63.6	1.6	4	19.0	1.70
DN 40	1½"	155.6	49.5	30.2	19.1	114.3	9.5	69.9	73.1	1.6	4	22.2	2.52
DN 50	2"	165.2	61.9	33.4	20.7	127.0	11.1	84.2	92.1	1.6	8	19.0	2.91
DN 65	2½"	190.6	74.6	38.2	23.9	149.2	12.7	100.0	104.8	1.6	8	22.2	4.38
DN 80	3"	209.6	90.6	42.9	27.0	168.2	14.3	117.5	127.1	1.6	8	22.2	5.90
DN 100	4"	254.1	116.0	47.7	30.2	200.0	15.9	146.1	157.2	1.6	8	22.2	9.72
DN 125	5"	279.5	143.7	50.9	33.4	234.9	15.9	177.9	185.8	1.6	8	22.2	12.31
DN 150	6"	317.6	170.6	52.4	34.9	269.8	15.9	206.4	216.0	1.6	12	22.2	15.75
DN 200	8"	381.1	221.4	61.9	39.7	330.2	20.6	260.4	269.9	1.6	12	25.4	24.41
DN 250	10"	444.6	276.3	66.7	46.1	387.3	19.0	320.7	323.9	1.6	16	28.5	34.37
DN 300	12"	520.8	327.1	73.1	49.3	450.8	22.2	374.7	381.1	1.6	16	31.7	50.26
DN 350	14"	584.3	359.1	76.3	52.4	514.3	22.3	425.5	412.8	1.6	20	31.7	70.11
DN 400	16"	647.8	410.4	82.6	55.6	571.5	25.4	482.7	470.0	1.6	20	34.9	88.89
DN 450	18"	711.3	461.7	89.0	58.8	628.6	28.6	533.5	533.5	1.6	24	34.9	109.46
DN 500	20"	774.8	513.0	95.3	62.0	685.8	31.7	587.4	584.3	1.6	24	34.9	135.23
DN 600	24"	914.5	615.9	106.4	68.3	812.8	36.5	701.7	692.2	1.6	24	41.2	202.83