



ANSI 300LBS FF BLIND

| Size | | Flange | | | Drilling | | Weight |
|--------|------|--------|------|-------|----------|----|---------|
| mm | inch | D | T | K | Bolt no. | H | Kg / Pc |
| DN 15 | ½" | 95 | 14.3 | 66.7 | 4 | 15 | 0.72 |
| DN 20 | ¾" | 117 | 15.1 | 82.5 | 4 | 19 | 1.15 |
| DN 25 | 1" | 124 | 17.5 | 88.9 | 4 | 19 | 1.51 |
| DN 32 | 1¼" | 133 | 19.1 | 98.4 | 4 | 19 | 1.92 |
| DN 40 | 1½" | 156 | 20.7 | 114.3 | 4 | 22 | 2.87 |
| DN 50 | 2" | 165 | 22.3 | 127 | 8 | 19 | 3.36 |
| DN 65 | 2½" | 190 | 25.4 | 149.2 | 8 | 22 | 5.08 |
| DN 80 | 3" | 210 | 28.6 | 168.3 | 8 | 22 | 7.13 |
| DN 100 | 4" | 254 | 31.8 | 200 | 8 | 22 | 11.96 |
| DN 125 | 5" | 279 | 35 | 234.9 | 8 | 22 | 16.05 |
| DN 150 | 6" | 318 | 36.6 | 269.9 | 12 | 22 | 21.63 |
| DN 200 | 8" | 381 | 41.3 | 330.2 | 12 | 25 | 35.25 |
| DN 250 | 10" | 444 | 47.7 | 387.3 | 16 | 29 | 54.32 |
| DN 300 | 12" | 521 | 50.8 | 450.8 | 16 | 32 | 80.33 |
| DN 350 | 14" | 584 | 54 | 514.3 | 20 | 32 | 107.33 |
| DN 400 | 16" | 648 | 57.2 | 571.5 | 20 | 35 | 140.23 |
| DN 450 | 18" | 711 | 60.4 | 628.6 | 24 | 35 | 178.30 |
| DN 500 | 20" | 775 | 63.5 | 685.8 | 24 | 35 | 224.89 |
| DN 600 | 24" | 914 | 69.9 | 812.8 | 24 | 41 | 344.56 |