



## JIS 16K FF BLIND

Size		Flange			Drilling		Weight
mm	inch	D	T	K	Bolt no.	H	Kg / Pc
DN 15	½"	95	12	70	4	15	0.60
DN 20	¾"	100	14	75	4	15	0.79
DN 25	1"	125	14	90	4	19	1.23
DN 32	1¼"	135	16	100	4	19	1.66
DN 40	1½"	140	16	105	4	19	1.80
DN 50	2"	155	16	120	8	19	2.10
DN 65	2½"	175	18	140	8	19	3.10
DN 80	3"	200	20	160	8	22	4.48
DN 100	4"	225	22	185	8	22	6.38
DN 125	5"	270	22	225	8	25	9.26
DN 150	6"	305	24	260	12	25	12.73
DN 200	8"	350	26	305	12	25	18.54
DN 250	10"	430	28	380	12	29	30.35
DN 300	12"	480	30	430	16	29	40.35
DN 350	14"	540	34	480	16	32	58.02
DN 400	16"	605	38	540	16	35	81.62
DN 450	18"	675	40	605	20	35	106.92
DN 500	20"	730	42	660	20	35	132.39
DN 550	22"	795	44	720	20	38	164.54
DN 600	24"	845	46	770	24	38	193.76