
PERONI KARYA SENTRA EST 1997

STAINLESS STEEL
150 LBS SCREWED FITTINGS
BSPP (ISO 228-1), BSPT (ISO 7-1), NPT THREAD


DIMENSION CONFORM TO ASME B16.3 AND ANSI/MSS SP-114-2018 WHERE APPLICABLE
MATERIAL CONFORM TO ASTM A351 GR. CF8 & CF8M
PRESSURE-TEMPERATURE RATINGS 300 PSI (-29 TO 66°C)
MADE BY LOST WAX INVESTMENT CASTING

UNION F.F TEFLON

Standard Pattern











PART T "A"






PART T "B"



PART T "C"





PART T "D"

SIZE	Total H (mm)	PART "A" D (mm)	PART "A" H (mm)	PART "A" M/S (mm)		PART "B" B (mm)	PART "B" D (mm)	PART "B" H (mm)	PART "C" A (mm)	PART "C" B (mm)	PART "C" H (mm)	PART "D" D (mm)	PART "D" H (mm)	PART "D" M/S (mm)		Weight Kg/Pc
¼"	38.0	30.0	15.6	24	1.5	23.9	18.3	18.1	23.7	15.7	1.5	18.0	19.6	24	1.5	0.10
⅜"	41.0	35.0	14.4	30	1.5	27.9	22.0	20.7	27.2	16.2	2.0	22.0	21.0	30	1.5	0.13
½"	42.5	43.0	17.3	36	2.0	33.4	27.0	20.0	32.5	21.5	2.0	27.0	23.0	36	2.0	0.19
¾"	48.0	47.0	18.8	42	2.0	38.3	32.0	23.4	37.3	26.3	2.0	32.0	25.9	42	2.0	0.26
1"	45.5	53.0	19.3	48	2.0	44.9	38.0	22.5	44.4	32.4	2.0	38.0	25.0	48	2.0	0.26
1¼"	58.5	71.0	25.9	62	2.0	59.3	49.0	27.8	59.0	47.0	2.0	49.0	32.5	62	2.0	0.72
1½"	64.0	77.0	24.6	68	2.0	65.5	58.4	31.5	64.4	52.4	2.0	58.4	32.6	68	2.0	0.74
2"	67.0	92.0	27.3	82	2.5	78.9	67.0	29.0	77.5	62.5	2.0	71.5	39.1	82	2.5	1.08
2½"	75.0	109.0	28.0	101	2.5	97.0	82.0	37.0	95.0	80.0	5.0	82.0	38.5	100	2.5	1.44
3"	90.0	122.0	29.0	114	2.5	110.5	96.0	45.0	107.0	92.0	5.0	96.0	47.0	114	2.5	2.00
4"	105.0	152.0	40.0	146	2.5	142.5	126.0	52.0	137.0	114.0	5.0	126.0	55.0	146	2.5	4.11

LAST UPDATED 26.09.2023