



## ANSI 300LBS RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95.3	14.3	66.6	35.0	1.6	4	15.8	0.65
DN 20	¾"	117.5	15.9	82.5	42.9	1.6	4	19.0	1.11
DN 25	1"	123.9	17.5	88.9	50.9	1.6	4	19.0	1.40
DN 32	1¼"	133.4	19.1	98.4	63.6	1.6	4	19.0	1.81
DN 40	1½"	155.6	20.7	114.3	73.1	1.6	4	22.2	2.69
DN 50	2"	165.2	22.3	127.0	92.1	1.6	8	19.0	3.22
DN 65	2½"	190.6	25.5	149.2	104.8	1.6	8	22.2	4.91
DN 80	3"	209.6	28.6	168.2	127.1	1.6	8	22.2	6.85
DN 100	4"	254.1	31.8	200.0	157.2	1.6	8	22.2	11.60
DN 125	5"	279.5	35.0	234.9	185.8	1.6	8	22.2	15.70
DN 150	6"	317.6	36.5	269.8	216.0	1.6	12	22.2	21.01
DN 200	8"	381.1	41.3	330.2	269.9	1.6	12	25.4	34.57
DN 250	10"	444.6	47.7	387.3	323.9	1.6	16	28.5	53.82
DN 300	12"	520.8	50.9	450.8	381.1	1.6	16	31.7	79.43
DN 350	14"	584.3	54.0	514.3	412.8	1.6	20	31.7	106.08
DN 400	16"	647.8	57.2	571.5	470.0	1.6	20	34.9	138.45
DN 450	18"	711.3	60.4	628.6	533.5	1.6	24	34.9	176.61
DN 500	20"	774.8	63.6	685.8	584.3	1.6	24	34.9	222.91
DN 600	24"	914.5	69.9	812.8	692.2	1.6	24	41.2	341.65