




DIN 2501 PN 40 RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	16	65	45	2	4	14	0.74
DN 20	¾"	105	18	75	58	2	4	14	1.06
DN 25	1"	115	18	85	68	2	4	14	1.29
DN 32	1¼"	140	18	100	78	2	4	18	1.89
DN 40	1½"	150	18	110	88	3	4	18	2.12
DN 50	2"	165	20	125	102	3	4	18	2.93
DN 65	2½"	185	22	145	122	3	8	18	4.00
DN 80	3"	200	24	160	138	3	8	18	5.22
DN 100	4"	235	24	190	162	3	8	22	7.17
DN 125	5"	270	26	220	188	3	8	26	10.28
DN 150	6"	300	28	250	218	3	8	26	14.00
DN 200	8"	375	34	320	285	3	12	30	26.46
DN 250	10"	450	38	385	345	3	12	33	43.32
DN 300	12"	515	42	450	410	4	16	33	62.55
DN 350	14"	580	46	510	465	4	16	36	87.56
DN 400	16"	660	50	585	535	4	16	39	124.39
DN 450	18"	685	50	610	615	4	20	39	132.92
DN 500	20"	755	56	670	615	4	20	42	181.78
DN 600	24"	890	62	795	615	5	20	48	280.39