



DIN 2573 PN 6

Size		Flange				Drilling		Weight
mm	inch	D	A	T	K	Bolt no.	H	Kg / Pc
DN 15	½"	80	22.0	12	55	4	11	0.40
DN 20	¾"	90	27.6	14	65	4	11	0.59
DN 25	1"	100	34.4	14	75	4	11	0.72
DN 32	1¼"	120	43.1	16	90	4	14	1.17
DN 40	1½"	130	49.0	16	100	4	14	1.36
DN 50	2"	140	61.1	16	110	4	14	1.50
DN 65	2½"	160	77.1	16	130	4	14	1.87
DN 80	3"	190	90.3	18	150	4	14	3.03
DN 100	4"	210	115.9	18	170	4	18	3.28
DN 125	5"	240	141.6	20	200	8	18	4.33
DN 150	6"	265	170.5	20	225	8	18	4.78
DN 200	8"	320	221.8	22	280	8	18	6.90
DN 250	10"	375	276.2	24	335	12	18	9.00
DN 300	12"	440	327.6	24	395	12	22	11.97
DN 350	14"	490	359.7	26	445	12	22	16.91
DN 400	16"	540	411.0	28	495	16	22	19.95
DN 450	18"	595	462.3	30	550	16	22	24.66
DN 500	20"	645	513.6	30	600	20	22	26.52